



IDRA 5S 5★

IDRA 5S

VENTILATED, PELLET FIRED, HYDRO STOVE



IDRA 5S		20	24
ENERGY CLASS		A++	A++
DIMENSIONS (WxDxH)	cm	59x68x122	59x68x122
HYDRO STOVE WEIGHT	kg	230	230
HEAT INPUT (min.-max.)	kW	6.8 - 20.1	8.4 - 24
NOMINAL HEAT OUTPUT (min.-max.)	kW	6.5 - 19.2	7.9 - 22.8
OUTPUT TO THE WATER (min.-max.)	kW	5.4 - 17.4	6.6 - 20.9
OUTPUT TO THE ENVIRONMENT (min.-max.)	kW	1.1 - 1.8	1.3 - 1.9
EXCHANGER WATER CONTENT	L	50	50
EXPANSION VESSEL	L	8	8
MAXIMUM OPERATING PRESSURE	bar	3	3
PUMP HEAD	m	6	6
WATER SIDE RESISTANCE (Δt 10 K) / (Δt 20 K)	mbar	123.5 / 30.9	186.8 / 46.7
EFFICIENCY (@ min.-max.)	%	95.9 - 95.6	94.9 - 94.2
MINIMUM CHIMNEY DRAUGHT	Pa	12	12
FLUE GAS DISCHARGE/AIR INTAKE DUCT DIAMETER	mm \varnothing	80 / 50	80 / 50
PELLET TANK CAPACITY	kg	38	38
PELLET CONSUMPTION min.-max.	kg/h	1.41 - 4.19	1.7 - 5.0
ELECTRIC ABSORPTION nominal/during ignition	W	72 - 320	83 - 345
HEATABLE VOLUME	m ³	440	510
NOISE	dB	35 / 50	35 / 50

Ventilated, pellet fired, hydro stove equipped with an exclusive high-performance combustion system. The presence of “Magic Glass” and its linear style also make it elegant and versatile.

PRODUCT PLUS



HYDRO VENTILATED



MAGIC GLASS



AUTOMATIC BRAZIER CLEANING



POWER MODULATION



REAR SMOKE OUTLET



WEEKLY PROGRAMMING

OPTIONAL



WI-FI



Black



White



Burgundy

