



ILDE 5★

VENTILATED PELLET STOVE



ILDE		8	10	10C ducted
ENERGY CLASS		A+	A+	A+
DIMENSIONS (WxDxH)	cm	49x56x110	49x56x110	49x56x110
STOVE WEIGHT	kg	100	100	100
HEAT INPUT (min.-max.)	kW	3.2 - 9.0	3.2 - 11.1	3.2 - 11.1
HEAT OUTPUT (min.-max.)	kW	3.1 - 8.1	3.1 - 9.8	3.1 - 9.9
EFFICIENCY (@ min.-max.)	%	94.5 - 90.7	94.5 - 88.9	94.5 - 88.9
MINIMUM CHIMNEY DRAUGHT	Pa	12	12	12
FLUE GAS EXHAUST DIAMETER	mm Ø	80	80	80
AIR INTAKE DUCT DIAMETER	mm Ø	50	50	50
PELLET TANK CAPACITY	kg	22	22	22
PELLET CONSUMPTION min.-max.	kg/h	0.67 - 1.85	0.67 - 2.30	0.67 - 2.30
Nominal ELECTRICAL ABSORPTION	W	40	41.6	61.6
ELECTRICAL ABSORPTION during ignition	W	281	281	281
HEATABLE VOLUME	m³	210	260	260

Steel-clad pellet stove with simple classic lines. Equipped with blown self-cleaning system that guarantees cleaning and constant combustion efficiency. Fast and time-efficient ignition is ensured by the quartz igniter. With the Touch display, all functions can be accessed easily and intuitively. The combustion chamber, made entirely of vermiculite, guarantees excellent performance. Self-cleaning ceramic glass with dedicated air. The “controlled negative pressure” operation and all installed devices ensure maximum comfort in complete safety. The versatility of the ducting system (mod. 10C), allows optimal warmth also in other rooms of the house.

PRODUCT PLUS



VENTILATED STOVE



DUCTED (mod. 10C)



CERAMIC GLASS



STEEL BRAZIER



POWER MODULATION



REAR SMOKE OUTLET



TOUCH DISPLAY



REMOVABLE HANDLE



DAILY / WEEKLY PROGRAMMING



“SILENT” FUNCTION



QUARTZ IGNITER



WI-FI U-in

OPTIONAL



AIR IONISER



ROOM TEMP. PROBE (mod. 10C)



REMOTE CONTROL



Black



White



Burgundy



APP-O BIOEN

