



MINORCA 2S 5★

MINORCA 2S

PELLET FIRED BOILER • HEATING ONLY OR WITH D.H.W. PRODUCTION (OPTIONAL)



MINORCA 2S		R20	R24	R34
ENERGY CLASS		A+	A+	A+
DIMENSIONS (WxDxH)	cm	87x60x137.2	87x60x137.2	87x60x137.2
BOILER WEIGHT	kg	382	385	390
HEAT INPUT (min.-max)	kW	6.5 - 22	6.5 - 26	6.5 - 33.3
HEAT OUTPUT (min.-max.)	kW	6 - 20.5	6 - 24.1	6 - 30.60
BOILER WATER CONTENT	L	73	73	73
EXPANSION VESSEL	L	12	12	12
MAXIMUM OPERATING PRESSURE	bar	2	2	2
PUMP HEAD	m	6	6	6
EFFICIENCY (@ min.-max.)	%	93.1 - 92.1	92.6 - 92.1	92.1 - 92
CHIMNEY DRAUGHT (min.-max.)	Pa	10/11	10/12	10/12
FLUE GAS EXHAUST DIAMETER	mm Ø	100	100	100
PELLET TANK CAPACITY	l/kg	92.7/60	92.7/60	92.7/60
PELLET CONSUMPTION min.-max	kg/h	1.37 - 4.59	1.37 - 5.39	1.37 - 6.95
MAXIMUM ABSORBED ELECTRICAL POWER	W	410	410	410
HEATABLE VOLUME	m³	133 - 455	133 - 535	133 - 680

Compact pellet boiler, with a large water content, equipped with an exclusive pellet dosing system that enables power to be delivered over wide modulation levels. The automatic cleaning system of the rotary brazier is innovative which effectively simplifies cleaning operations. Production of D.H.W. via optional kit.

PRODUCT PLUS



HEATING ONLY BOILER



AUTOMATIC BRAZIER CLEANING



POWER MODULATION



TOP SMOKE OUTLET



REAR SMOKE OUTLET



DAILY / WEEKLY PROGRAMMING



DOUBLE STAR + FEEDING SCREW SYSTEM

OPTIONAL



WI-FI



D.H.W. PRODUCTION

