

VENTILATED PELLET STOVE











ADNA		8	10C ducted	13C ducted
ENERGY CLASS		<b>A</b> +	A+	<b>A</b> +
DIMENSIONS (WxDxH)	cm	58x59x112	58x59x112	58x59x112
STOVE WEIGHT	kg	120	120	120
HEAT INPUT (minmax.)	kW	3.2 - 9	3.2 - 11.1	5.3 - 13.6
HEAT OUTPUT (minmax.)	kW	3.1 - 8.1	3.1 - 9.9	4.9 - 12.2
EFFICIENCY (@ minmax.)	%	94.5 - 90.7	94.5 - 88.9	93.4 - 89.5
MINIMUM CHIMNEY DRAUGHT	Pa	12	12	12
FLUE GAS EXHAUST DIAMETER	mm Ø	80	80	80
AIR INTAKE DUCT DIAMETER	mm Ø	50	50	50
PELLET TANK CAPACITY	kg	20	20	20
PELLET CONSUMPTION minmax.	kg/h	0.67 - 1.85	0.67 - 2.30	1.09 - 2.82
Nominal ELECTRICAL ABSORPTION	W	40.1	91.6	93.4
ELECTRICAL ABSORPTION during ignition	W	281	281	281
HEATABLE VOLUME	m³	210	260	320

A pellet stove with a circular design and ceramic inserts that enhance its elegance and prestige. Rounded sides in black steel and hearth glass of "Magic" type, beyond the fire door, for a greater scenic effect even when the stove is switched off. Equipped with blown self-cleaning system that guarantees cleaning and constant combustion efficiency. Quartz igniter for quick ignition. With the hand-held remote control and integrated room sensor, optimum management of room temperature as well as various functions is possible. The combustion chamber, made entirely of vermiculite, guarantees excellent performance. Selfcleaning glass with dedicated air. The "controlled negative pressure" operation and all installed devices ensure maximum comfort in complete safety. The versatility of the ducting system (mod. 10C-13C), allows optimal warmth also in other rooms of the house.

## PRODUCT PLUS



**VENTILATED** STOVE



**DUCTED** (mod. 10C-13C)



MAGIC **GLASS** 



STEEL **BRAZIER** 

OUTLET



**POWER** MODULATION



FITTING 130/80





RADIO CONTROL WITH ROOM PROBE



**REMOVABLE** HANDLE



DAILY / WEEKLY **PROGRAMMING** 



"SILENT" **FUNCTION** 



QUARTZ **IGNITER** 



## **OPTIONAL**



ROOM TEMP. PROBE (mod. 10C-13C)



Black







